

XTRACYCLE®



HOOPTIE




- INSTRUCTIONS
- WARRANTY
- SAFETY PRECAUTIONS

WARRANTY

Hoopties are guaranteed to be free from manufacturing defects for one (1) year from the original date of purchase. This warranty applies only to the original buyer and is not transferable. This warranty does not cover damage from use of this product outside of its intended range or that resulting from modification or neglect. It also does not cover wear and tear resulting from the normal use of the product. Please contact your Xtracycle dealer if you believe you have a warranty claim.

HOOPTIE INSTALLATION INSTRUCTIONS

- 1** Prep your bicycle by installing rear bridge, RackLocks, V-Racks, and CarryAlls.
- 2** Take Hooptie upright (the one with the wider base goes in front) and press mounting bracket over bosses on EdgeRunner racks. Fit should be snug, but should be easy to move by hand. Align holes in Hooptie mounting bracket with holes in bosses on EdgeRunner V-Racks.
- 3** Repeat this step on 2nd Hooptie upright. With holes aligned, you are now ready to install your FlightDeck.
- 4** To install the FlightDeck, find the 4 large M6 bolts with washers and nuts.




- 5** Put washer on top of the deck and one under the Hooptie mounting bracket and EdgeRunner bosses. Tighten bolts and nuts using appropriate tools (4mm allen key and 10mm wrench). Tighten all bolts to 6-10 N-m. Do not over tighten. Check tightness regularly.



- 6** Insert 4 short M5 bolts through the FlightDeck. They will thread directly into the bosses in the middle of the EdgeRunner racks. Tighten with a 3mm allen key.



- 7** With uprights installed, your Hooptie is ready to accept the two handrails. Hooptie hand rails are interchangeable - they are not sided. Insert each in handrail into the front and rear uprights evenly. You may have to loosen the bolts on the previous step in order for side rails to slide in easily. Make sure you tighten all bolts after adjustment.



- 8** Hooptie rails have 2 settings - narrow and wide. The narrow setting will work without a Yepp child seat. The wide setting will work when Yepp seats are installed - align the bosses on the Hooptie uprights with desired setting hole settings in handrails. (If no Yepp seat is installed, the narrower Hooptie setting is recommended).



- 9** Screw M5 rail securing bolts with lock washer into Hooptie uprights with 3mm allen key. Screws are designed to insert through holes in Hooptie handrails.



- 10** Your Hooptie is now ready for use.

⚠ WARNING: Before each ride, check tightness of all hardware - push and pull on all elements of Hooptie to identify any loose hardware.

⚠ WARNING: Use your best judgment in selecting routes, and choosing how to place your children on the bike. Always use Hooptie handlebars and U-Tube foot rests when riding with passengers not in a child seat.

⚠ WARNING: Passengers not in a kids seat must hold onto the inner rail of the Hooptie at all times while on an Xtracycle. Never allow passengers to place their hands on the outer Hooptie rail.

View the Xtracycle Owner's Manual at xtracycle.com/support for additional safety guidelines when riding with passengers or cargo.